

 <p><b>Polyurethane</b></p>	Model	OD X ID	Standard Length	Min. Bending	temperature	Pressure range	Color
	PU0425	4mm x 2.5mm	100m	10	0~50 C	0~10 Kg/cm2 (Kpa)	BU:Blue BK:Black OR:Orange RE:Red Y:Yellow CL:CLEAR
	PU0640	6mm x 4mm	100m	16			
	PU0850	8mm x 5mm	100m	22			
	PU1065	10 mmx 6.5mm	100m	28			
	PU1280	12mmx 8mm	100m	37			
	PU1410	14mm x 10mm	100m	60			

 <p><b>Nylon</b></p>	Model	OD X ID	Standard Length	Min. Bending	temperature	Pressure range	Color
	NL0320	3mm x 2mm	100m	10	0~50 C	0~16 Kg/cm2 (Kpa)	BK:Black MW:MilK White
	NL0425	4mm x 2.5mm	100m	16			
	NL0640	6 mmx 4mm	100m	22			
	NL0860	8mm x 6mm	100m	28			
	NL1075	10 mmx 7.5mm	100m	37			
	NL1290	12mm x 9mm	100m	60			
NL1411	14mm x 11mm	100m	80				

 <p><b>Coil hose</b></p>	Model	OD X ID	Standard Length	Min. Bending	temperature	Pressure range	Color
	PUC0604	6 x 4	6, 9, 12, 15 m	40	40~80 C	0~16 Kg/cm2 (Kpa)	Y:Yellow OR:Orange BU:Blue
	PUC0805	8 x 5	6, 9, 12, 15 m	50			
	PUC1065	10 x 6.5	6, 9, 12, 15 m	60			
	PUC1208	12 x 8	6, 9, 12, 15 m	84			
PUC1410	14 x 10	6, 9, 12, 15 m	84				

 <p><b>PU Braided Hose</b></p>	Model	OD X ID	Standard Length	BuHigh Pressure	Blasting pressure	Operating temperature	Color
	PU-H 4X6	4mm X 6mm	100m	Working Pressure up to 300 PSI(20kg)	900 PSI (60-80 kg)	-40 C to +80 C	OR:Orange BU:Blue
	PU-H 4X7	5 mmX 8mm	100m				
	PU-H 4X8	10 x 6.5	100m				
PU-H 4X9	8 X 12	100m					

 <p><b>PTFE Tube</b> PTFE(Milky white) FEP(Transparent)</p>	Model	OD X ID	Standard Length	Operating temp.Range:	Working Pressure 23 c	Color
	TFL2.5 X4	4mmX2.5	200m	50 c~+280 c	10 Bar	MW:MilK White
	TFL4X6	6mmX4	100m			
	TFL6X8	8mmX6	100m			
	TFL8X10	10mmX8	100m			
	TFL10X12	12mmX10	100m			
TFL14X16	16mm14	100m				